

**FB20EX-11 – FB30-11**

Item		Unit	FB20EX-11	FB25EX-11	FB20EXG-11	FB25EXG-11	FB30-11	
<b>• Performance</b>								
Rated capacity		kg	2000	2500	2000	2500	3000	
Load center		mm	500	500	500	500	500	
Std. mast lift height	A	mm	3000	3000	3000	3000	3000	
Lifting speed (loaded)		mm/s	290	260	290	260	260	
Travel speed (unloaded)		km/h	16.5	16.0	16.5	16.0	14.0	
Max. gradeability (loaded)		% (degree)	19.0 (11.0)	16.0 (9.0)	19.0 (11.0)	16.0 (9.0)	16.0 (9.0)	
<b>• Dimensions, weight</b>								
Overall length (with std. forks)		B	mm	3175	3365	3325	3480	3590
Overall width (at tire, single)		C	mm	1165	1165	1165	1165	1235
Overall height	Mast lowered		mm	1995	1995	1995	1995	2015
	Overhead guard	D	mm	2095	2095	2220	2220	2215
Free lift (overall mast height)		E	mm	150	155	150	155	155
Fork length		F	mm	920	1070	920	1070	1070
Wheelbase		G	mm	1400	1400	1550	1550	1600
Service weight (with standard battery)		kg	3530	3960	4100	4230	5090	
<b>• Motor output</b>								
Drive		kw/h	AC 10.3	AC 10.3	AC 10.3	AC 10.3	AC 9.7	
Pump		kw/5min	DC 10.0	DC 10.0	DC 10.0	DC 10.0	DC 12.6	
PS		kw/h	DC 0.6	DC 0.6	DC 0.6	DC 0.6	DC 0.6	
<b>• Tire size</b>								
Front tires		–	23x9-10-16PR	23x9-10-16PR	23x9-10-16PR	23x9-10-16PR	28x9-15-14PR	
Rear tires		–	18x7-8-14PR	18x7-8-14PR	18x7-8-14PR	18x7-8-14PR	21x8-9-10PR	

